

DH-HCVR4104/4108C-S2

4/8CH Tribrid 720P-Lite Smart 1U HDCVI DVR



Features

- > Support HDCVI/Analog/IP Video input
- > H.264 dual-stream video compression
- > HCVR4104/4108C-S2: All channel 720P recording
- > HDMI/VGA simultaneous video output
- > 4/8 channel synchronous playback, GRID interface & smart search
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc.
- > ONVIF Version 2.4 conformance
- > Support 1 SATA HDD up to 4TB, 2 USB2.0
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)

DH-HCVR4104/4108C-S2


Technical Specifications

Model		DH-HCVR4104C-S2		DH-HCVR4108C-S2	
System					
Main Processor		Embedded processor			
Operating System		Embedded LINUX			
Video					
Input		4 channel, BNC		8 channel, BNC	
Standard	HDCVI	720P HDCVI Camera			
	Analog	NTSC/PAL			
	IP	Support 2ch 1080P/720P IP Camera			
Audio					
Input		1 channel, RCA			
Output		1 channel, RCA			
Two-way Talk		Reuse audio input/output channel 1			
Display					
Interface		1 HDMI, 1 VGA			
Resolution		1920×1080, 1280×1024, 1280×720, 1024×768			
Display Split		1/4		1/4/8/9	
Privacy Masking		4 rectangular zones (each camera)			
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording			
Recording					
Video/Audio Compression		H.264/G.711			
Record Rate	Main Stream:	720P/960H/D1(1~25/30fps)		1*720P(1~25/30fps)+7*(1~15fps)/960H/D1 (1~25/30fps)	
Bit Rate		80~4096Kb/s			
Record Mode		Manual, Schedule(Regular(Continuous), MD), Stop			
Record Interval		1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec			
Video Detection					
Trigger Events		Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips			
Video Detection		Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank			
Playback & Backup					
Sync Playback		1/4		1/4/9	
Search Mode		Time/Date, MD & Exact search (accurate to second)			
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom			
Backup Mode		USB Device/Internal SATA burner/Network			
Network					
Ethernet		RJ-45 port (10/100M)			

DH-HCVR4104/4108C-S2

Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P	
Max. User Access	128 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
Storage		
Internal HDD	1 SATA port, up to 4TB	
Auxiliary Interface		
USB Interface	2 ports(2 Rear), USB2.0	
General		
Power Supply	DC12V/1.5A	DC12V/2A
Power Consumption	10W(without HDD)	
Working Environment	-10℃ ~ +55℃ / 10%~90%RH / 86~106kpa	
Dimension(W×D×H)	Smart 1U, 205mm×205mm×40mm	
Weight	0.5KG(without HDD)	

System Connection



*Takes HCVR4104C-S2 as an example

Dahua Technology Co., Ltd.

1199' BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2015 Dahua Technology Co., Ltd.