

HIGH VISION



SPECIFICATION

Model	PTZ-2MP-18X
Camera	
Image Sensor	1/2.8" SONY Low Illumination CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.264+/H.265/MJPEG
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	120°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/S
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	5.35mm-96.3mm
Focus Control	18X Optical Zoom
Night Vision	
Infrared LED	30μx6PCS
IR Range	60m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Stream type	Main Stream / Sub Stream / MJPEG
AI Function	
Smart Analytic	3D Human Tracking、 Intrusion Detection、 Alarm Detection
Tracking effective range	5~45M Speed: 3~12KM/h
Interface	
Audio	2-Way Audio
Alarm	/
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	-40℃~+70℃
Operating Humidity	≤90% Non Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	18.5x 18.5 x 28.8 (cm)
Weight	2.2Kgs